



003

The **super-resistant** curtain cord with **ultra-limited stretch!**

Its **pre-stretched** aramid fibre core (Kevlar) gives it unrivalled **strength** as well as **extremely limited elongation** under load. It is therefore ideal for equipping **single** and **double tracks** with a **motorised pull**.

Available in **7 diameters**, this curtain rope can also be used for a range of technical applications, such as suspending particularly **heavy loads**.

Its elegant black braided 16-ply outer in heavy-duty **UV-treated** polyester makes it usable both **indoors** and **outdoors**.

► Technical specifications

Reference	ADKo3	ADKo4	ADKo5	ADKo6	ADKo8	ADK10	ADK12
Diameter (mm)	3	4	5	6	8	10	12
Weight (g/m)	7.5	12	18	29	42	66	85
Roll length (m)	100	100	100	100	100	100	100
Weight (kg/roll)	0.9	1.4	2.2	3.3	4.6	7.8	9.7
Elongation under load (%)	1.5	1.5	1.5	1.5	1.5	1.5	1.5
Tensile strength at break (daN)	430	745	900	1019	1621	2900	3000
Tensile strength at break (kg)	438	759	917	1039	1652	2957	3059
Composition	Outer: Heavy-duty polyester fibres with UV-resistant treatment Core: Kevlar aramid fibres						
Construction	16-ply						

CONTACT OUR EXPORT TEAM

+33 (0)6 23 21 50 28



export@azur-scenic.com

The information in this document provides generic values that describe only the standard technical specifications and chemical composition of the products concerned. No guarantee is offered. Any images are non-contractual. The names of the colours are given for information purposes only and do not guarantee a specific colour.